



Scooter Expert 2T

Oil for 2 stroke engines Scooters

Technosynthese – Anti Smoke

TYPE OF USE

All scooters daily used in the city.

Suitable for direct injection 2 stroke engines or conventional carburettor.

Can be used with oil injection systems or in premix. Suitable for all type of fuel leaded or unleaded.

Compatible with catalytic converters.

PERFORMANCES

NORMES

API TC

APPROVALS

JASO FC under N° 033MOT047

Technosynthese engine oil developed for scooter engines running at high rpm, outstanding oil film resistance for anti wear protection.

Avoid deposits and ensure engine cleanliness at all levels: combustion chamber, spark plug, top of the piston, ring grooves, exhaust port, exhaust pipe...

RECOMMENDATIONS

Mixing ratio : from 2% to 4% (from 50:1 to 25:1) according to manufacturers' requirements and adjust according to your own use.

PROPERTIES

Colour	Visual	Green
Density à 20°C (68°F)	ASTM D1298	0.856
Viscosity at 100°C (212°F)	ASTM D445	8.0 mm ² /s
Viscosity at 40°C (104°F)	ASTM D445	45.3 mm ² /s
Viscosity grade	ASTM D2270	150
Pour Point	ASTM D97	-30°C / -22°F
Flash point	ASTM D92	88°C / 190°F
TBN	ASTM D2896	0.96 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty. – Made in France

MOTUL . 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel : 33 1 48 11 70 00 - FAX : 33 1 48 33 28 79 . Site Web : www.motul.fr

09/10