

# 100% Synthetic – Ester – Anti-Smoke

# TYPE OF USE

Any high performance 2 stroke bikes, sports bikes, replicas, trails, off road bikes, enduro, mopeds... fitted with high performance 2 stroke engines, running at high rpm in severe conditions, direct injection or carburetor.

Suitable for oil injector systems or premix, leaded or unleaded gasoline Compatible with catalytic converters.

Other uses: Scooters, ATV...

## PERFORMANCE

| STANDARDS | API TC – JASO FD - ISO-L-EGD |
|-----------|------------------------------|
| APPROVAL  | JASO FD under N°033MOT064    |

100% synthetic lubricant, Ester technology, specially engineered for high performance engines running at high rpm, perfect oil film resistance to protect against wear.

Improved power output, minimize engine internal friction.

Japanese JASO standard consists in passing 4 engine bench tests in order to evaluate lubricity, detergency, anti-smoke and anti-deposit lubricant properties. JASO FD performance is the highest level of JASO standard, improved engine cleanliness compared to JASO FC.

Formulation built on synthetic bases with very high combustion properties which minimize smoke and deposits.

Instantaneous and stable mixing with gasoline.

### RECOMMENDATIONS

Mixing ratio: from 2% to 4% (from 50:1 to 25:1) according to manufacturers' requirements. Adjust according to your own use.

### PROPERTIES

Color Density at 20°C (68°F) Viscosity at 40°C (104°F) Viscosity at 100°C (212°F) Viscosity index Flash point TBN Visual ASTM D1298 ASTM D445 ASTM D445 ASTM D2270 ASTM D92 ASTM D2896 Green. 0.862 46.4 mm²/s 8.9 mm²/s 175 88°C / 190.4°F 2.15 mg KOH/g