

Mobil Super 2000 X1 10W-40

Premium Semi-Synthetic Passenger Vehicle Engine Oil

Product Description

The Mobil Super 2000 range of lubricants are enhanced-premium semi-synthetic engine oils, designed to provide a superior level of protection and performance .

Features and Benefits

Mobil Super 2000 products are industry proven so you can trust you will get the performance you want from your vehicle.

Mobil Super 2000 X1 provides:

- Superior wear protection
- Superior engine cleanliness
- Superior high temperature protection
- Superior cold temperature protection

Applications

Mobil Super 2000 products are formulated to give you confidence of protection beyond that of conventional oils. We particularly recommend Mobil Super 2000 if you occasionally experience demanding driving conditions:

- Nearly all engine technologies
- Gasoline and Diesel
- Passenger cars, SUV's, light trucks and vans
- Highway cruising and stop and go city driving
- Normal to occasionally severe operating conditions
- High Performance Engines

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

Mobil Super 2000 X1 meets or exceeds the following 10W-40 industry and builder specifications:

API SL/SJ/CF	X
ACEA A3/B3	X
Quality Level: 500 00	X

Mobil Super 2000 X1 has the following builder 10W-40 approvals:

VW 505 00	X
-----------	---



Mobil Super 2000 X1 has the following builder approvals:	10W-40
MB-Approval 229.1	X

Typical Properties

Mobil Super 2000 X1	10W-40
Viscosity, ASTM D 445	
cSt @ 40° C	97
cSt @ 100°	14.4
Sulfated Ash, wt%, ASTM D 874	0.91
Phosphorous	0.144
Flash Point, °C, ASTM D 92	230
Density @15° C kg/l, ASTM D 4052	0.87
Pour Point, °C, ASTM D 97	-30

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet, or will be provided by seller to customers if and as legally required. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus and Mobil Super are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.