



# Scooter Expert 4T 10W-40

4 stroke engine oil Scooters and Maxi Scooters

Technosynthese®

## TYPE OF USE

Specifically designed for scooters and maxi-scooters fitted with 4 stroke engines, displacement from 50cc to 650cc, with or without catalytic converters.

All scooters used downtown in the city.

Suitable for leaded or unleaded fuel.

## PERFORMANCES

STANDARDS

API SL

APPROVALS

JASO MA under N° M033MOT105

Technosynthese® oil, reinforced with a synthetic base stock which provides outstanding protection.

JASO MA approval ensures perfect operating conditions when a wet clutch is fitted on the scooter.

Excellent high temperature resistance particularly indicated for city use: full load during long periods and idling at traffic lights.

The SAE 10W-40 viscosity grade corresponds to the most recent manufacturers' recommendations and improves engine starts when cold while lowering wear.

Very low volatility to reduce oil consumption.

Ensures engine cleanliness, detergent and dispersive properties and resistance to viscosity increase from unburned deposits produced by the engine. Aging resistance.

Anti-oxidation, Anti-corrosion, Anti-foam properties.

## RECOMMENDATIONS

Drain interval: according to manufacturers' recommendations and tune to your own use.

Can be mixed with synthetic or mineral oils.

## PROPERTIES

Viscosity grade	SAE J 300	<b>10W-40</b>
Density at 20°C (68°F)	ASTM D1298	0.874
Viscosity at 40°C (104°F)	ASTM D445	95.4 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D445	14.9 mm <sup>2</sup> /s
Viscosity index	ASTM D2270	164
Pour point	ASTM D97	-33°C / -27°F
Flash point	ASTM D92	228°C / 442°F
TBN	ASTM D2896	7.9 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel : 33 1 48 11 70 00 - Fax : 33 1 48 33 28 79 - Web Site : [www.motul.fr](http://www.motul.fr)

07/12